

3 IN 1 PARKAS ICEBERG

Ref. 5ICEB



Range Seasons



SIZES AND COLORS

Color	Size S	Size M	Size L	Size XL	Size XXL
RED Iceberg 3/1	5ICEBS	5ICEBM	5ICEBL	5ICEBXL	5ICEBXXL
Barcodes	3435245501017	3435245501024	3435245501031	3435245501048	3435245501055

GENERAL DESCRIPTION AND MATERIALS

- Outshell : **100 % polyamid Ripstop** **breathable PU coating, sealed seams, inserts** in 100% polyamide breathable PU coating
- **Waterproof : 2000mm**
- **Breathable : 3000mvp**
- Lining : 100% polyamide taffetas
- **Removable micro fleece jacket, 100 % polyester**
- High-necked collar
- **Lined, concealed and removable hood.**
- Cap form
- Wrapped closing on the neck by a large double scratch closing
- **Two-ways zipper with 2 flaps** : 1 with snap fastener, 1 with gutter

- **Sleeves** : adjustable wrist by scratch
- **Back protection**
- **Elastic waist** with outside block-cord on sides
- **Elastic bottom** tightened by inside block-cord on sides
- 2 pockets at the bottom, horizontal with zipper and flap
- 2 pockets at the top, oblique with zipper and flap
- 1 inside pocket for mobile



SPECIFIC ADVANTAGES

- **Removable inside jacket**
- **Breathable**
- **Sealed seams**
- **Warm clothing**
- **Lined, concealed and removable hood**
- **A sewed rigid shaft allows hood's well bearing**
- **Tightening hood** and efficient hood closing
- **Two-ways zipper** for more comfort when sitting
- **Waterproofness** because of a gutter concealed in the inside flap that allows the water flows and avoids infiltrations
- **Tightening cuffs**
- **Back protection**
- **Waist tightening**
- **Bottom tightening**
- **Many pockets**

MAIN APPLICATION FIELDS

- **Cold** places
- **Outdoor** jobs
- **Wet** places
- **Rain**

PACKAGING

- **Individual** packing
- **10 parkas** in a box

STANDARDIZATION

This garment is in conformity with applicable provisions of Annexe II, at the end of book III, Title I of fourth part of "Code du travail" and with article R 4312-23 of the same Code and, with the European standard **EN 340 and EN 14058** in accordance with Article R4311-12 of the same Code.

EN14058:2004**1/3** (Thermal resistance)**3/3** (Air permability)X
X
X**EN340:2003****Washing instruction**

Max : 30 x